

R28 Wirefree RTS Motor

Motorization

The R28 Wirefree RTS motor installs in minutes and is perfect for small windows in locations where electrical connections are not available. The external rechargeable battery pack allows the motor to charge without removing the shade.


SPECIFICATIONS

Minimum Shade Width **19"**
 Maximum Shade Width **80"**
 Maximum Weight **8.8 lbs**
 Tube Sizes Available **37mm**

MOTOR COMPONENT OPTIONS

External Li-Ion Rechargeable Battery Pack
- Charger required

Power Cable **10" motor lead with quick disconnect plug**
 Control Options **Wireless Wall Switch**
Wireless Remote
Universal Interface
Timer
Sun sensor
mylink™ RTS Smartphone and Tablet Interface, voice controlled with Amazon Alexa



FOR OPTIMAL PERFORMANCE, THE ANTENNA MUST BE EXPOSED, SHOULD NOT COME IN CONTACT WITH METAL SURFACES, AND SHOULD NOT BE CUT.

TECHNICAL FEATURES

Voltage Supply **12V DC**
 Index Protection Rating **IP 20**
 Limit Switch Type **Electronic**
 Temperature Working Range **32°F to 140°F (0°C to 60°C)**
 Insulation Class **Class III**
 Antenna **Radio frequency antenna wire**
 —must be exposed
 —should not come in contact with metal surfaces
 —should not be cut

PERFORMANCE

Torque **1.1 Nm**
 Speed **28 rpm**
 Amps **2**
 Radio Frequency **433.42 MHz**
 Radio Frequency Control Range **65 feet**

External Li-Ion Rechargeable Battery Pack

Approximate charge time 2–4 hours.
 The charger plugs into a standard wall outlet or extension cord.

Dimensions: 9.8125" x 1" x 0.9"

